

# CTS aluminium tent structure with double sloped roof



**The CTS aluminium tent structures with double sloped roofs are designed for fast deployment on any type of terrain.**

CTS structures can fulfil multiple functions : accommodation tents, catering (MESS) tents, recreation centres, storage facilities or hospitals.

CTS tents are made of an extruded aluminium frame and a cover made of flame retardant PVC coated polyester.

The structures are equipped with base plates and mounting parts made of galvanized steel.

The lightweight structures of different spans are easy and quick to install (3 persons and one day are necessary for the installation of a catering structure for 90 people). Worldwide service and assistance are provided by our specialised technicians.

Available options :

- White translucent or opaque cover.
- Internal separation walls.
- Rigid access doors, single or double.
- Windows.
- Lighting.
- Heating.
- Air conditioning.
- Ventilation.
- Electric systems.
- False ceiling, awning, interior insulation.
- Floor based on cassette system, optional load capacity of 500 daN/m<sup>2</sup>.

Load resistance :

- Wind : 100 km/h
- Snow : 10 daN/m<sup>2</sup>







Span width (m)	10 m	15 m	20 m	25 m	30 m	40 m	50 m
Wall height (m)	2.50 / 3.00 / 4.00	2.50 / 3.00 / 4.00	2.50 / 3.00 / 4.00	4.00	3.00 / 4.00	4.00 / 5.00	4.00 / 5.00
Width per module (m)	5.00	5.00	5.00	5.00	5.00	5.00	5.00
Height (m)	4.67 / 5.22 / 5.86	5.12 / 5.67 / 6.67	5.93 / 6.48 / 7.48	8.29	8.12 / 9.12	10.80 / 11.80	12.45 / 13.45
Assembly time for a length of Hours	10 m x 50 m 9 h	15 m x 50 m 10 h	20 m x 50 m 10 h	25 m x 50 m 15 h	30 m x 50 m 16 h	40 m x 55 m 23 h	50 m x 55 m 28 h
Number of people	4	5	6	6	8	10	10
Packing for a length of 50 m	1 x 20'	1 x 20'	1 x 40'	1 x 40'	1 x 40'	2 x 40'	2 x 40'
Weight (kg)	3,409	6,226	7,464	9,100	14,920	20,679	31,300

NOTE : We reserve the right to make changes and alterations that optimise our products or to ensure they correspond to the latest technology and specifications.

France  
 Losberger Rapid Deployment Systems SAS  
 58 A rue du Dessous des Berges  
 75013 Paris  
 Phone: +33 1 46 72 42 69  
 Fax: +33 1 46 58 91 79  
 E-Mail: info@losberger-rds.com  
 www.losberger-rds.com

Germany  
 Losberger RDS GmbH  
 Fölfeld · Gottlieb-Daimler-Ring 14  
 74906 Bad Rappenau  
 Phone: +49 7066 980-0  
 Fax: +49 7066 980-232  
 E-Mail: rds@losberger.com  
 www.losberger-rds.com

Losberger brands : Losberger, Bachmann, TMB

